

# Master-PUR L FishTec

Article Master No.: 012553

PU suction hose / transport hose, lightweight, very good flexibility, microbe-resistant and hydrolysis-resistant, food-safe according to FDA





food approved

medium heavy

m pressure resistant

## **Product Details**

**Construction / Material** 

flexible

- Type of construction: profile extruded hose with plastic spiral
- Spiral Design: made from plastic, as hard as PVC
- Execution of the wall: made of pure material, made of specified material, wall thickness between the spirals approx. 0,6 mm to 0,8 mm
- Material of the wall: Polyether Polyurethane
- Specifications of the wall: meets FDA code for food contact: 21 CFR 177.1550, 21 CFR 177.2600, 21 CFR 175.300, 21 CFR 175.105, 21 CFR 176.170, 21 CFR 176.180

#### Properties

- Chemical Properties: odourless and tasteless, good resistance to chemicals, good UV resistance, good ozone resistance, halogen-free, hydrolysis resistant, microbe-resistant, plasticiser-free
- Flexibility: flexible
- Weight: medium heavy
- Pressure Resistance: pressure resistant
- Colour: blue, RAL5015
- Other: particularly smooth on the inside

#### **Operating Temperature**

**Delivery Information** 

**Application Areas** 

 Areas of application: Agriculture, Bulk & Construction, Sea & Rail transport, Food & Pharma, Waste Disposal & Cleaning Technology

**Customizing Options** 

# Article Variants

| Extended Article<br>Number | Article<br>number | Nominal Size<br>(DN)<br>mm | Bending<br>radius*<br>mm | Weight<br>kg/m | Max. Production<br>length<br>m | wall thickness<br>min.<br>mm | wall thickness<br>max.<br>mm | Length (standard lengths available<br>for order)<br>m |
|----------------------------|-------------------|----------------------------|--------------------------|----------------|--------------------------------|------------------------------|------------------------------|---|
| 012553-076-x               | 012553            | 76                         | 100                      | 0,6            | 30.00                          | 0,6                          | 4,2                          | 10  |
| 012553-102-x               | 012553            | 102                        | 140                      | 0,87           | 30.00                          | 0,6                          | 4,8                          | 10  |
| 012553-152-x               | 012553            | 152                        | 200                      | 1,61           | 20.00                          | 0,7                          | 5,8                          | 10  |
| 012553-203-x               | 012553            | 203                        | 260                      | 2,41           | 20.00                          | 0,7                          | 7,2                          | 10  |
| 012553-254-x               | 012553            | 254                        | 300                      | 3,57           | 10.00                          | 0,8                          | 8                            | 10  |
| 012553-305-x               | 012553            | 305                        | 350                      | 4,52           | 10.00                          | 0,8                          | 8,2                          | 10  |

## **Delivery Variants**

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## **Disposal instructions**

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

#### **Possible Connection Elements**



Combiflex PU threaded connector, fixed cast-on fixed PU threaded connector for all Master-PUR L, Master-PUR H and Master-PUR HX hose types, based on DIN ISO 228



Combiflex Cast-on PU Fixed Flange Fixed PU flange for all Master-PUR hoses, for counterflanges to DIN 2632 / DIN 2633 / DIN 2673



Combiflex Cast-on PU Swivel Flange Fixed cast-on PU loose flange for all Master-PUR hoses, for counterflanges to DIN 2632 / DIN 2633 / DIN 2673

#### Individual consultation

We offer consultation by phone: +49 209 97077-112

Product requests via masterflex.de/en

## Address Headquarters

Masterflex SE Willy-Brandt-Allee 300 45981 Gelsenkirchen

